

# LIVE PERFORMANCE REINFORCEMENT



**LIVE 1202** Professional  
12-Channel/ 2-Bus (4 Mono 4 Stereo) Mixer

**LIVE 802** Professional  
8-Channel/ 2-Bus (4 Mono 4 Stereo) Mixer



## Features LIVE 802

- 5 XLR inputs with DNA™ microphone preamps
- Dynamic compression (channels 1-2)
- 3-band EQ plus 2 aux sends per channel
- 60mm faders with mute switch and LED
- USB audio connectivity with level control
- 100 Alesis DSP effects
- Balanced XLR, balanced/unbalanced 1/4" outputs
- 9-band graphic EQ for main or monitor outputs
- Headphone out with independent level control

## Features LIVE 1202

- 7 XLR inputs with DNA™ microphone preamps
- Dynamic compression (channels 1-4)
- 3-band EQ plus 2 aux sends per channel
- 60mm faders with mute switch and LED
- USB audio connectivity with level control
- 100 Alesis DSP effects
- Balanced XLR, balanced/unbalanced 1/4" outputs
- 9-band graphic EQ for main or monitor outputs
- Headphone out with independent level control

## Technical Specifications

<b>Mono Input channels</b>	<b>Microphone Inputs :</b> Electronically balanced, discrete input configuration <b>Frequency Response :</b> 20 Hz to 20 kHz, ±0.5 dB <b>THD+N :</b> <0.005% at 0 dBu, 1 kHz <b>Gain Range :</b> 0 dB to 45 dB (Mic) <b>SNR :</b> 105 dB	<b>Main Mix</b>	<b>Noise (bus noise) :</b> Fader 0 dB, channels muted: -102 dB (ref: +4 dBu) Fader 0 dB, all input channels assigned & set to unity gain: -91 dB (ref: +4 dBu) <b>Phantom Power :</b> Mic Pin2/Pin3 and Pin1 47±2V
<b>Line Inputs</b>	<b>Electronically Balanced</b> <b>Frequency Response :</b> 20 Hz to 20 kHz, ±0.25 dB <b>THD+N :</b> <0.005% at 0 dBu, 1 kHz <b>Sensitivity Range :</b> -15 dBu to 30 dBu	<b>DSP Section (DFX)</b>	<b>A/D &amp; D/A Converters :</b> 24-bit <b>DSP Resolution :</b> 24-bit <b>Effects :</b> 10 DSP effects families with 10 variations available per family <b>Presets :</b> 100 total <b>Controls :</b> Rotary encoder to select preset, DSP mute switch, peak LED indicator
<b>Impedances</b>	<b>Microphone Inputs :</b> 51.1 KΩ <b>Channels Insert Return :</b> 200 KΩ <b>All Other Inputs :</b> >100 KΩ <b>2-Track Outputs :</b> 10 KΩ <b>All Other Outputs :</b> 20 KΩ	<b>Power Supply</b>	<b>Main Voltag :</b> 100-240 VAC ~50/60 Hz
<b>Equalization</b>	<b>High-Shelving :</b> ± 15 dB @ 12 kHz <b>Mid-Bell (mono) :</b> ± 15 dB @ 2.5 kHz <b>Low-Shelving :</b> ± 15 dB @ 80 Hz <b>Main EQ :</b> 9 EQ bands (63 Hz, 125 Hz, 250 Hz, 500 Hz, 1 kHz, 2 kHz, 4 kHz, 8 kHz, 16 kHz), ± 15 dB	<b>Dimensions (width x depth x height)</b>	<b>802 :</b> 12.0" x 13.6" x 3.1", 305 mm x 346 mm x 80 mm <b>1202 :</b> 14.1" x 13.6" x 3.1", 358 mm x 346 mm x 80 mm
		<b>Weight</b>	<b>802 :</b> 7.7 lbs., 3.5 kg <b>1202 :</b> 9.0 lbs., 4.1 kg

All features & specifications subject to change without notice. © Natthapong Sales & Service Co., Ltd.

**Distributor :**

**บริษัท นัฐพงษ์ เซลล์ไอออนเทคเซอร์วิส จำกัด**  
**Natthapong Sales & Service Co., Ltd.**

สำนักงานใหญ่ : 119,119/1 ถนนอภัยวงศ์ แขวงพญาภิรมย์ พระนคร กรุงเทพฯ 10200  
โทรศัพท์ : 0-2225-0094, 0-2623-8899 (อัตโนมัติ 18 เลขหมาย) โทรสาร : 0-2226-4020  
สาขาเชียงใหม่ : ชั้น G (ด้านในสุด) 99 หมู่ 8 ถนนพหลโยธิน ต.สุเทพ อ.สุเทพ จ.เชียงใหม่ 12130 โทรศัพท์ : 0-8998-7379 (อัตโนมัติ 10 เลขหมาย) โทรสาร : 0-8998-7380  
[www.mynpe.com](http://www.mynpe.com) E-Mail: [mynpe@mynpe.com](mailto:mynpe@mynpe.com)



May 2014

[http://twitter.com/Natthapong\\_NPS](http://twitter.com/Natthapong_NPS)  
<http://www.facebook.com/mynpethailand>

