

PROFESSIONAL POWER MIXER



PROFESSIONAL P.A. SOUND SYSTEM PROFESSIONAL P.A. SOUND SYSTEM PROFESSIONAL P.A. SOUND SYSTEM PROFESSIONAL P.A.



Features

- ▶ Professional Mixer With Power Amplifier and 70,100V Line Voltage Output
MDA-800MT 800Wmax, MDA-1000MT 1000Wmax
- ▶ Selectable 5 Mic./Line Input
- ▶ Built-in Bluetooth/USB/SD MP3 Player & FM Tuner (87.50-108MHz.)
- ▶ 1 Line Telephone Link
- ▶ Digital Echo
- ▶ Selectable Power Supply 220Vac and 24Vdc
- ▶ Complete Protection System

SPECIFICATION

MDA-800MT

MDA-1000MT

Frequency Response: @ 4 Ω Mic Input @ 0, -3 dB Aux Input, Amp Input @ 0, -3 dB	50 Hz - 10 kHz 40 Hz - 10 kHz	
Frequency Response: @ 100 V Mic Input @ 0, -3 dB Aux Input, Amp Input @ 0, -3 dB	50 Hz - 10 kHz 40 Hz - 10 kHz	
Horn High Pass Filter:	125 Hz 6 dB / Octave	
Channel Equalizer: Shelving ±12 dB Shelving ±12 dB	Low 70 Hz High 12 kHz	
Master Equalizer: Shelving ±12 dB Peaking ±13 dB Shelving ±12 dB	Low 70 Hz Mid 2.5 kHz High 12 kHz	
Hum & Noise: @ 20 Hz - 20 kHz, 8 Ω Mic Input Aux Input Amp Input	< -24 dBu < -29 dBu < -44 dBu	< -20 dBu < -28 dBu < -45 dBu
Input Impedance: Mic Input Aux Input Amp Input	2.2 kΩ 62 kΩ 37 kΩ	
Input Sensitivity: @ 8 Ω Mic Input Aux Input Amp Input	-51 dBu -12 dBu 0 dBu	
Maximum Input Level: Mic Input Aux Input Amp Input	-29 dBu +10 dBu 0 dBu	
Distortion THD+N: @ 8 Ω, 1 kHz	3% (500 Wrms)	4% (750 Wrms)
Power Output Maximum: @ 8 Ω / THD < 30%	800 Wrms	1,000 Wrms
Output Indicator:	On, TP, -13, -8, -3, 0, +3 dB	
Power Requirement:	220 V 50 Hz, 24 Vdc	
Power Consumption: Idle Rate Power @ 8 Ω	70 W 1,200 W	70 W 1,700 W
Cooling:	2 Fan Left to Right	
AC Fuse:	T8 A	T10 A
DC Fuse:	T50 A	
Dimensions / Packing Dimensions: (W x H x D)	483 x 132 x 445 mm / 531 x 230 x 574 mm	
Net Weight / Gross Weight:	30.6 kg (67.32 lbs) / 32.4 kg (71.28 lbs)	34.2 kg (75.24 lbs) / 35.9 kg (78.98 lbs)

Note: 0dBu=0.775Vrms, 0dBV=1Vrms

All features & specifications subject to change without notice. © NPE Industry (Thailand) Co.,Ltd. (R1) 22 September 2023

บริษัท นัฐพงษ์ เซลส์แอนด์เซอร์วิส จำกัด
Natthapong Sales & Service Co.,Ltd.

สำนักงานใหญ่ : 119,119/1 ถนนอภัยวงศ์ แขวงปทุมวัน เขตปทุมวัน กรุงเทพมหานคร 10200
โทรศัพท์ : 0-2225-0094, 0-2623-8899 (อัตโนมัติ 18 เลขหมาย) โทรสาร : 0-2226-4020
สาขาเชียงใหม่ : ชั้น G (ด้านในสุด) 99 หมู่ 8 ถนนพหลโยธิน ต.สุทนต์ อ.ลำลูกกา จ.ปทุมธานี 12130 โทรศัพท์ : 0-2992-7379 โทรสาร : 0-2992-7380
สาขาสายลม : 9/8 หมู่ 2 ถนนบางกอกน้อย-นครชัยศรี ต.บางเตย อ.สามพราน จ.นครปฐม 73210 โทรศัพท์ : 0-2889-5496-8 โทรสาร : 0-2889-5866
E-Mail : mynpn@mynpn.com www.mynpn.com



@mynpethailand

