COMPACT STEREO MIXER WITH DIGITAL ECHO

NPE® AUDIO PRODUCTS



MU-802E MP3
ROTARY LEVEL



MU-1203S MP3
SLIDE LEVEL

Stereo Mixer

- 3-Band EQ, Built-In Digital Echo Processor
- Bluetooth / USB / SD Card MP3 Player & FM Tuner with Remote Control
- 9 LED Tri-Coloured Metering
- Stereo Mix Out, Stereo Monitor Out, Stereo REC Out
- External AC Adaptor

SPECIFICATIONS	MU-802E MP3	MU-1203E MP3	MU-802S MP3	MU-1203S MP3
Frequency Response: Mic / Line Input to any Audio Output	Min Gain 20Hz - 20kHz 0, - 0.5dB Max Gain 80Hz - 20kHz 0, - 0.5dB			
Frequency Response: Stereo Input to any Audio Output	25Hz - 20kHz 0, -2dB			
Distortion THD+N @1kHz + 20dBu:	< 0.05% Any input to audio output			
Channel Equalizer:	LF 100Hz, HF 10kHz ±15dB Shelving MF 2.5kHz ±15dB Peaking			
Equivalent Input Noise (EIN) @20Hz - 20kHz:				
MIC / Line Input Ref 150Ω	-125dBu			
Line Input	-82dBu			
Stereo Input	-91dBu			
Hum & Noise @20Hz - 20kHz (Echo Off):				
Any Max Gain & EQ Flat	-44dBu	-41dBu	-44dBu	-41dBu
Master Min	-93dBu	-91dBu	-93dBu	-90dBu
Common Mode Rejection Ratio (CMRR):				
MIC / Line Input Ref 150Ω	> 56dB			
Line Input	> 36dB			
Stereo Input	> 33dB			
GAIN ref PGM, Monitor Output @100kΩ:				
Microphone Input	29dB to 70dB			
Line Input	-8dB to 33dB			
Stereo Input	6dB to 21dB			
Return Input	16dB			
Difference PGM Output SEND & REC Output:	15dB			
Maximum Input Level (Min Gain):				
Microphone Input	+5dBu			
Line Input	+41dBu			
Stereo Input	+27dBu			
Return Input	+21dBu Min			
Input Impedance:				
Microphone Input	2kΩ Balanced			
Line Input	136kΩ Balanced			
Stereo Input	47kΩ Balanced			
Return Input	20kΩ Unbalanced			
Output Impedance:	150Ω Any audio output			
Channel Peak Indication:	6dB Before Clipping			
Output Level Indication:	0.775Vrms (0dBu)			
BLUETOOTH Frequency Response @0, -3dB:	60Hz - 15kHz			
Version	3.0			
FM Tuner Frequency:	87.5MHz - 108MHz			
Step	0.1MHz			
MP3 Player Frequency Response @0, -3dB:	30Hz - 15kHz			
Port	USB Drive / SD Card 32GB Max			
Dimensions (WxHxD):	288x64x294mm	372x64x294mm	288x68x346mm	372x68x346mm
Net Weight:	3.7kg(8.14lbs)	4.5kg(9.9lbs)	4.3kg(9.46lbs)	5.1kg(11.22lbs)
Power Requirement AC Adapter 220V to 18Vct:	12W			

Note: 0dBu=0.775Vrms, 0dBV=1Vrms

All features & specifications subject to change without notice. © NPE Industry (Thailand) Co.,Ltd April 2018

Distributor :
บริษัท นัฐพงษ์ เซลส์แอนด์เซอร์วิส จำกัด
Natthapong Sales & Service Co.,Ltd.
สำนักงานใหญ่ : 119,119/1 ถนนอัษฎางค์ วังบูรพาภิรมย์ พระนคร กรุงเทพฯ 10200
โทรศัพท์ : 0-2225-0094,0-2623-8899 (อัตโนมัติ 18 เลขหมาย) โทรสาร : 0-2226-4020
สาขาเชียรรังสิต : ชั้น G (ด้านในสุด) 99 หมู่ 8 ถนนพหลโยธิน ต.คูคต อ.ลำลูกกา จ.ปทุมธานี
12130 โทรศัพท์ : 0-2992-7379 โทรสาร : 0-2992-7380
สาขาศาลายา : 9/8 หมู่ 2 ถนนบางกอกน้อย-นครชัยศรี ต.บางเตย อ.สามพราน จ.นครปฐม
73210 โทรศัพท์ : 0-2889-5496-8 โทรสาร : 0-2889-5866
www.mynpe.com E-Mail :mynpe@mynpe.com

NPE BEST BUY The TECHNOLOGY CITY

@mynpethailand