

Line Array Speakers Sound System


SPECIFICATIONS	NLA-112
Frequency Response	60Hz - 18KHz ±3dB
Crossover Frequency	1kHz
Drivers	Low 1x12" / 3" Voice Coil High 1x1.4" / 3" Voice Coil Compression
Rate Power	Low 450Wrms 900Wpeak, High 125Wrms.
Maximum SPL	125dB continuous, 131dB peak
Sensitivity	Low 97dB /1W/1M, High 110dB /1W/1M
Impedance	Low 8Ω, High 8Ω
Dispersion	75°H x 15°V
Construction	18mm enclosure pu paint 2 recessed carrying handles
Grille	Heavy duty powder coated perforated steel mesh
Connectors	2 x Speakon NL4
Dimensions (HxWxD)	320 x 681 x 452 mm
Net Weight	31kg

NLA-112
2-ways Line Array Speakers

NBP-18
Sub Bass 18"

SPECIFICATIONS	NBP-18
Components	1x18" (475mm) LF driver
Frequency Response	30-160Hz ±6dB
Power Handling	Passive 800 watts rms., 1,600 watts peak
Sensitivity	100dB, 1 watt @ 1 metre
Maximum SPL	123dB continuous, 130dB peak
Crossover	Active : recommended point 80-150Hz, 24dB/octave LR (depending on application)
Nominal Impedance	8Ω
Construction	19mm (3/4") birch plywood throughout; rebated, Finished in black textured paint. Four recessed carrying handles. Four stacking feet
Grille	Heavy duty powder coated perforated steel mesh
Connectors	(2) Speakon NL4MP wired pin1+: positive, pin1+: negative
Spares and Accessories	OMEGA PRO 18 18" (476mm) LF loudspeaker
Dimensions (HxWxD)	825 x 575 x 870 mm
Net Weight	78kg

Note: 0dBu=0.775Vrms, 0dBV=1Vrms

All features & specifications subject to change without notice. ©NPE Industry (Thailand) Co.,Ltd September 2015

Distributor :

บริษัท นัฐพงษ์ เซลส์แอนด์เซอร์วิส จำกัด
Natthapong Sales & Service Co.,Ltd.

สำนักงานใหญ่ : 119,119/1 ถนนอภัยวงศ์ แขวงปทุมวัน เขตปทุมวัน กรุงเทพมหานคร 10200
 โทรศัพท์ : 0-2225-0094, 0-2623-8899 (อัตโนมัติ 18 เลขหมาย) โทรสาร : 0-2226-4020
 สาขาเชียงใหม่ : ชั้น G (ด้านในสุด) หมู่ 8 ถนนพหลโยธิน ตำบล อ.ลำลูกกา จ.ปทุมธานี 12130
 โทรศัพท์ : 0-2992-7379 (อัตโนมัติ 10 เลขหมาย) โทรสาร : 0-2992-7380
<http://www.facebook.com/myNPE.thailand> http://twitter.com/Natthapong_NPS

www.myNPE.com
 E-Mail: myNPE@myNPE.com

