



BACK



PT-300A/PT-208 POWERED SPEAKER MP3

PT-208/PT-300A ตัวลำโพงขยายเสียงเคลื่อนที่พร้อมลำโพง

- ใช้สำหรับการเรียนการสอน การบรรยายโฆษณาและประกาศเสียง
- มีเครื่องเล่น MP3 Player มี LCD พร้อมระบบ FM
- กำลังขยายเสียง 520W pmpo
- ตัวตู้ทำด้วยไม้อัดอย่างดีแข็งแรงทนทาน มีช่องสำหรับใส่ขาตั้งปรับระดับด้านล่าง
- **PT-300A** มีลำโพงในตัวขนาด 12 นิ้ว 1 ตัว Horn Tweeter 1 ตัวและมีหูหิ้วด้านข้าง
- **PT-208** มีลำโพงในตัวขนาด 8 นิ้ว 2 ตัวและมีหูหิ้วด้านบน
- ใช้ MIC ได้ 2 ช่อง, AUX/TAPE ได้ 2 ช่องพร้อมปุ่มปรับเสียงทุ้ม-แหลมและ RECORD 1ช่อง

SPECIFICATION	PT-300A	PT-208
Mic Inputs : Type Connectors Impedance Sensitivity Frequency Response Maximum Level THD+Noise Signal-to-Noise Ratio Common Mode Rejection	Active Balanced/Unbalanced 1/4"TRS 20kΩ min -52dBu 200Hz-15kHz, -3dB -19dBu <0.1%@1kHz60W8Ω 65dB ref. 65W 8Ω 60dB	Active Balanced/Unbalanced 1/4"TRS 20kΩ min -55dBu 200Hz-15kHz, -3dB -19dBu <0.2%@1kHz50W4Ω 62dB ref. 65W 4Ω 60dB
Aux Input : Type Connectors Impedance Sensitivity Frequency Response Maximum Level THD+Noise Signal-to-Noise Ratio	Unbalanced Stereo RCA 7.5kΩ -10dBu 15Hz-15kHz 0,-3dB >20dBu <0.05% 1kHz 60W 8Ω 85dB ref. 65W 8Ω	Unbalanced Stereo RCA 7.5kΩ -13dBu 15Hz-15kHz 0,-3dB >20dBu <0.1% 1kHz 50W 4Ω 82dB ref. 65W 4Ω
Tone Control Bass Treble	±12dB @80Hz Shelving ±12dB @12kHz Shelving	±12dB @80Hz Shelving ±12dB @12kHz Shelving
Record Output : Type Connectors Impedance Gain	Unbalanced Stereo RCA 1kΩ Ref. Aux input+10dB 65Wrms (520Wpmpo)	Unbalanced Stereo RCA 1kΩ Ref. Aux input+10dB 65Wrms (520Wpmpo)
Power Amplifier output		
MP3 Player & Radio MP3 Input Source FM Frequency range FM step Frequency	SD Card, USB 87.5MHz-108MHz 100KHz	SD Card, USB 87.5MHz-108MHz 100KHz
Speaker : Type Frequency Response Dimensions: (WxHxD)Net/Shipping Weight: Net/Shipping Power:Requirement/Consumption	Woofer 12"8Ω, Tweeter 3"8Ω 50Hz-15kHz+/-3dB 380x585x375mm./408x630x408mm. 18.2kg/(40.04lbs)/20.2kg(44.44lbs) 220Vac /130VA	Full range coaxial 8"8Ωx2 60Hz-12kHz+/-3dB 250x520x250mm./273x570x273mm. 9.8kg(21.56lbs)/11kg(24.2lbs) 220Vac /110VA

All features & specifications subject to change without notice. ©NPE Industry (Thailand) Co.,Ltd March 2011
Distributor :

 บริษัท นัทธพงษ์ เซลส์แอนด์เซอร์วิส จำกัด
Natthapong Sales & Service Co.,Ltd.

สำนักงานใหญ่ : 119,119/1 ถนนอักษะทางค์ วัชรบุรีพาณิชย์ พระนคร กรุงเทพฯ 10200
โทรศัพท์ : 0-2225-0094, 0-2623-8899 (อัตโนมัติ 18 เลขหมาย) โทรสาร : 0-2226-4020
สาขาเชียงราย : ชั้น 6 (ด้านในสุด) 99 หมู่ 8 ถนนพหลโยธิน ต.สุคต อ.ลำลูกกา จ.ปทุมธานี
12130 โทรศัพท์ : 0-2992-7379 โทรสาร : 0-2992-7380

www.mynpe.com : www.facebook.com/mynpethailand
E-Mail : mynpe@mynpe.com

Note : 0dBu = 0.775Vrms, 0dBV = 1Vrms

www.mynpe.com

E-Mail: mynpe@mynpe.com

